

Bambu Lab X1E

Technical Specification

Body

Build Volume:	256*256*256 mm ³
Chassis:	Steel
Shell:	Aluminum & Glass

Supported Filament

PLA, PETG, TPU, PVA, BVOH:	Optimal
ABS, ASA, PC, PA, PET:	Superior
Carbon/Glass Fiber Reinforced PLA, PETG, PA, PET, PC, ABS, ASA:	Superior
PPA-CF/GF, PPS, PPS-CF/GF:	Ideal

Heating

Active Chamber Heating:	Yes
Maximum Chamber Control Temperature:	60 °C

Air Purification

Pre-filter grade:	G3
HEPA filter grade:	H12
Activated Carbon Filter type:	Coconut Shell Granulated
VOC Filtration:	Optimal
Particulate Matter Filtration:	Yes

Network Control

Ethernet:	Yes
Wireless Network:	Wi-Fi
Network Kill Switch:	Wi-Fi & Ethernet
Removable Network Module:	Yes
802.1X Network Access Control:	Yes

Cooling

Part Cooling Fan:	Closed Loop Control
Hot End Fan:	Closed Loop Control
Control Board Fan:	Closed Loop Control
Chamber Temperature Regulator Fan:	Closed Loop Control
Auxiliary Part Cooling Fan:	Closed Loop Control

ToolHead

Hot End:	All-Metal
Extruder Gears:	Hardened Steel
Nozzle:	Hardened Steel
Max Hot End Temperature:	320 °C
Nozzle Diameter (Included):	0.4 mm
Nozzle Diameter (Optional):	0.2 mm, 0.6 mm, 0.8 mm
Filament Cutter:	Yes
Filament Diameter:	1.75 mm

Heatbed

Build Plate:	Flexible Steel Plate
Compatible Build Plate:	Bambu Textured PEI Plate, Bambu Smooth PEI Plate Bambu High Temperature Plate, Bambu Cool Plate
Max Build Plate Temperature:	110°C@220V, 120°C@110V

Speed

Max Speed of Toolhead:	500 mm/s
Max Acceleration of Toolhead:	20 m/s ²
Max Hot End Flow:	32 mm ³ /s @ABS(Model: 150*150mm single wall; Material: Bambu ABS; Temperature: 280°C)

Sensors

Bambu Micro Lidar:	Yes
Chamber Monitoring Camera:	1920*1080 Included
Door Sensor:	Yes
Filament Run Out Sensor:	Yes
Filament Odometry:	Optional with AMS
Power Loss Recover:	Yes

Physical Dimensions

Dimensions:	389*389*457 mm ³
Net Weight :	16 kg

Electrical Requirements

Voltage:	100-240 VAC, 50/60 Hz
Max Power:	1400W@220V, 750W@110V

Electronics

Display:	5-inch 1280*720 Touch Screen
Storage:	4GB EMMC and Micro SD Card Reader
Control Interface:	Touch Screen, APP, PC Application
Motion Controller:	Dual-Core Cortex M4
Application Processor:	Quad ARM A7 1.2 GHz
Neural-Network Processing Unit:	2 Tops

Software

Slicer:	Bambu StudioSupport third party slicers which export standard G-code such as SuperSlicer, PrusaSlicer and Cura, but certain advanced features may not be supported.
Slicer Supported OS:	macOS, Windows

Wi-Fi

Frequency Range:	2412 MHz - 2472 MHz (CE) 2412 Mhz - 2462 MHz (FCC) 2400 MHz - 2483.5 MHz (SRRC)
Transmitter Power (EIRP):	≤ 21.5 dBm (FCC) ≤ 20 dBm (CE/SRRC)
Protocol:	IEEE 802.11 b/g/n

Ethernet

Socket:	RJ45
Speed:	100 Mbps / Full Duplex

Laser (CLASS 1)

Wavelength:	850 nm, 850 nm
Maximum Output of Laser Radiation:	< 0.778 mW